


## TP6/97 Axial Component Forming Machine:

	MM		INCH	
	Min	Max	Min	Max
<b>TP6/1/97 Standard Model Specifications:</b>				
<b>P</b>	6.5	60	0.255	2.362
<b>B</b>	4.0	13.0	0.157	0.511
<b>c</b>	1.2	-	0.047	-
<b>L</b>	-	50	-	1.968
<b>d</b>	0.4	1.3	0.015	0.051
<b>D</b>	0.4	16.0	0.015	0.629


**Product Order Code: MOL20.OL01/97**



### TP6/4/97 Extra Reinforced Bending Model Specifications:

<b>P</b>	10.16	60	0.4	2.362
<b>B</b>	5.0	13.0	0.196	0.511
<b>c</b>	2.4	-	0.094	-
<b>L</b>	-	50	-	1.968
<b>d</b>	0.6	14.0	0.023	0.550
<b>D</b>	0.6	16.0	0.023	0.629

**Product Order Code: MOL20.OL04/97**



### TP6/6/97 Reduced Bending Variable Specifications:

<b>P</b>	5.08	60	0.2	2.362
<b>B</b>	4.0	13.0	0.157	0.511
<b>c</b>	0.8	-	0.031	-
<b>L</b>	-	50	-	1.968
<b>d</b>	0.4	0.8	0.015	0.031
<b>D</b>	0.4	10.0	0.015	0.393

**Product Order Code: MOL20.OL06/97**

