

## Sumake End of Line Pneumatic Screwdrivers:

### CA 90° Angle Pneumatic Screwdriver Range:

This new range of Pneumatic Screwdrivers from Sumake have been designed with the user in mind. Many patents have been filled in the manufacture of these new Air Screwdrivers and have won several awards. This Air Screwdriver is compact in size with a soft composite ergonomic grip - A new high technology patented MSC motor that produces 30% more power than a normal Pneumatic Screwdriver. A new one pulse 3% tolerance cross path patented clutch system. One Handed Operation, External Torque Setting, Low Vibration, Reversible, Energy Saving. These Pneumatic Screwdrivers come complete with 4 extra colour coded torque locking covers for ease of torque setting identification on larger assembly lines with many Screwdrivers. This range of Screwdrivers require an oiled air supply.



Model No	Speed (Rpm)	Air Hose Bore (6Kg/Cm <sup>2</sup> ) (mm)	Air Hose Bore (5Kg/Cm <sup>2</sup> ) (mm)	Torque Range (Kgf-Cm)	Machine Screw (mm)	Screwdriver Bit Size	Quantity Available	Price (Exc. VAT)
CA10	1000	5.00	5.00	0.5-2.00	1.0-2.2	Hex 6.35mm (1/4")	1	£100.00
CA20	1000	5.00	5.00	1.0-8.00	1.7-3.3	Hex 6.35mm (1/4")	1	£100.00
CA30	1800	5.00	6.35	3.0-17.0	2.2-4.2	Hex 6.35mm (1/4")	1	£100.00
CA35	2200	5.00	6.35	3.0-20.0	2.4-4.5	Hex 6.35mm (1/4")	1	£100.00
CA40	1000	5.00	6.35	5.0-30.0	2.8-5.0	Hex 6.35mm (1/4")	1	£100.00
CA45	800	6.35	8.00	8.0-40.0	3.0-5.7	Hex 6.35mm (1/4")	2	£100.00
CA48	1800	8.00	9.50	5.0-45.0	2.8-5.8	Hex 6.35mm (1/4")	2	£100.00
CA50	1400	8.00	9.50	7.0-50.0	2.9-6.0	Hex 6.35mm (1/4")	1	£100.00

### CBP Pistol Grip Pneumatic Screwdrivers:

This new range of Pneumatic Screwdrivers from Sumake have been designed with the user in mind and are supplied in a choice of 2 sizes. Many patents have been filed in the manufacture of these new Air Screwdrivers and have won several awards. Features include a patent clutch with only 3% deviation torque. A wide ranging torque capacity with durable motor and ergonomic design. The special mechanical design includes a patent motor, low noise, low vibration and high accuracy. These Air Screwdrivers have a comfortable anti-slide exterior in soft resin. \*Denotes small body size.



Model No	Speed (Rpm)	Noise Level (+/-2dBA)	Air Hose Bore (mm)	Air Consumption (m <sup>3</sup> /min)	Torque Range (Kgf-Cm)	Machine Screw (mm)	Screwdriver Bit Size	Quantity Available	Price (Exc. VAT)
CBP35*	2200	72	5.00	0.28	3.0-20.0	2.4-4.5	Hex 6.35mm (1/4")	3	£100.00
CBP38*	1800	72	5.00	0.28	3.0-25.0	2.4-4.7	Hex 6.35mm (1/4")	3	£100.00
CBP41*	1000	72	5.00	0.28	5.0-35.0	2.8-5.2	Hex 6.35mm (1/4")	1	£100.00
CBP45	800	74	9.50	0.55	8.0-45.0	3.2-5.8	Hex 6.35mm (1/4")	2	£100.00
CBP47*	550	72	5.00	0.28	10.0-50.0	3.6-6.0	Hex 6.35mm (1/4")	2	£100.00
CBP48	1800	74	9.50	0.55	7.0-50.0	2.8-6.0	Hex 6.35mm (1/4")	6	£100.00
CBP50	1400	78	9.50	0.55	10.0-60.0	2.9-6.2	Hex 6.35mm (1/4")	1	£100.00
CBP55	1000	78	9.50	0.55	12.0-75.0	3.5-6.6	Hex 6.35mm (1/4")	6	£100.00
CBP60	550	78	9.50	0.55	30.0-110.0	5.0-7.3	Hex 6.35mm (1/4")	4	£100.00
CBP65	300	78	9.50	0.55	30.0-180.0	5.7-9.5	Hex 6.35mm (1/4")	1	£100.00

### CCP Cushion Grip Pneumatic Screwdrivers:

Introducing a further addition to the existing range of Sumake Pneumatic Screwdrivers, the new cushion Air Screwdriver with many user friendly features. This new Pneumatic Screwdriver has a precision adjustment in the gearing, rotation system and a smooth, efficient direction change which is operated by a push valve reverse button.



Model No	Speed (Rpm)	Noise Level (dB)	Air Consumption (Cfm)	Air Consumption (L/min)	Torque Range (Nm)	Screwdriver Bit Size	Quantity Available	Price (Exc. VAT)
CCP48	1700	78	1.90	55	1.5-6.0	Hex 6.35mm (1/4")	1	£100.00



### Lever Start Pneumatic Screwdrivers:

**CL Lever Start Range:** This new range of Pneumatic Screwdrivers from Sumake have been designed with the user in mind. Many patents have been filed in the manufacture of these new Air Screwdrivers and have won several awards. This Air Screwdriver is compact in size with a soft composite ergonomic grip - A new high technology patented MSC motor that produces 30% more power than a normal Air Screwdriver. Features of this Air Screwdriver Range include: One Handed Operation, External Torque Adjustment, Low Vibration, Reversible and Energy Saving. This range of screwdrivers requires an oiled air supply. All of these Pneumatic Screwdrivers have a Torque Tolerance of +/- 3%.

Model No	Speed (Rpm)	Noise Level (dB)	Air Consumption (m <sup>3</sup> /min)	Torque Range (Kgf-Cm)	Machine Screw (mm)	Screwdriver Bit Size	Quantity Available	Price (Exc. VAT)
CL10	1000	72	0.20	0.5-2.0	1.0-2.2	Hex 6.35mm (1/4")	2	£100.00
CL30	1800	74	0.28	3.0-17.0	2.2-4.2	Hex 6.35mm (1/4")	2	£100.00
CL35	2200	74	0.28	3.0-20.0	2.4-4.5	Hex 6.35mm (1/4")	2	£100.00
CL45	800	78	0.30	8.0-40.0	3.0-5.7	Hex 6.35mm (1/4")	2	£100.00
CL48	1800	78	0.55	5.0-45.0	2.8-5.8	Hex 6.35mm (1/4")	2	£100.00
CL60	550	78	0.55	15.0-95.0	4.1-7.0	Hex 6.35mm (1/4")	2	£100.00

### Push Start Pneumatic Screwdrivers:

**CP Push Start Range:** This new range of Pneumatic Screwdrivers from Sumake have been designed with the user in mind. Many patents have been filed in the manufacture of these new Air Screwdrivers and have won several awards. This Air Screwdriver is compact in size with a soft composite ergonomic grip - A new high technology patented MSC motor that produces 30% more power than a normal Air Screwdriver. Features of this Air Screwdriver Range include: One Handed Operation, External Torque Adjustment, Low Vibration, Reversible and Energy Saving. This range of drivers requires an oiled air supply. All of these Pneumatic Screwdrivers have a Torque Tolerance of +/- 3%.



Model No	Speed (Rpm)	Noise Level (dB)	Air Consumption (m <sup>3</sup> /min)	Torque Range (Kgf-Cm)	Machine Screw (mm)	Screwdriver Bit Size	Quantity Available	Price (Exc. VAT)
CP10	1000	72	0.20	0.5-2.0	1.0-2.2	Hex 6.35mm (1/4")	1	£100.00
CP30/OE	1800	-	0.28	2.0-16.0	2.2-4.2	Hex 6.35mm (1/4")	1	£100.00
CP45/OE	800	-	0.30	8.0-40.0	3.6-5.7	Hex 6.35mm (1/4")	1	£100.00
CP60	550	78	0.55	15.0-95.0	4.1-7.0	Hex 6.35mm (1/4")	2	£100.00
CP60/OE	550	-	0.55	15.0-95.0	4.1-7.0	Hex 6.35mm (1/4")	2	£100.00
CP65	300	78	0.60	30.0-180.0	5.7-9.5	Hex 6.35mm (1/4")	3	£100.00

## Pneumatic Pistol Grip Screwdrivers

**CPP Pistol Grip Pneumatic Screwdrivers** - This new range of Pneumatic Screwdrivers from Sumake have been designed with the user in mind and are supplied in a choice of 2 sizes. Many patents have been filed in the manufacture of these new Air Screwdrivers and have won several awards. Features include a patent clutch with only 3% deviation torque. A wide ranging torque capacity with durable motor and ergonomic design. The special mechanical design includes a patent motor, low noise, low vibration and high accuracy. These Air Screwdrivers have a comfortable anti-slide exterior in soft resin. \*Denotes small body size.



Model No	Speed (Rpm)	Noise Level (+/-2dBA)	Air Hose Bore (mm)	Air Consumption (m <sup>3</sup> /min)	Torque Range (Kgf-Cm)	Machine Screw (mm)	Screwdriver Bit Size	Quantity Available	Price (Exc. VAT)
CPP30	1800	72	6.0	0.55	3.0-25.0	2.4-4.7	Hex 6.35mm (1/4")	1	£100.00
CPP35*	2200	72	5.0	0.28	3.0-20.0	2.4-4.5	Hex 6.35mm (1/4")	8	£100.00
CPP40	1000	72	6.0	0.55	5.0-35.0	2.8-5.2	Hex 6.35mm (1/4")	1	£100.00
CPP45	800	74	6.0	0.55	8.0-45.0	3.2-5.8	Hex 6.35mm (1/4")	1	£100.00
CPP47*	550	72	5.0	0.28	10.0-50.0	3.6-6.0	Hex 6.35mm (1/4")	2	£100.00
CPP48	1800	74	6.0	0.55	7.0-50.0	3.1-6.0	Hex 6.35mm (1/4")	10	£100.00
CPP50	1400	78	6.0	0.55	10.0-60.0	3.6-6.3	Hex 6.35mm (1/4")	3	£100.00
CPP55	1000	78	6.0	0.55	12.0-75.0	3.8-6.6	Hex 6.35mm (1/4")	4	£100.00
CPP60	550	78	6.0	0.55	30.0-110.0	5.0-7.8	Hex 6.35mm (1/4")	1	£100.00
CPP65	300	78	6.0	0.60	30.0-170.0	5.0-9.0	Hex 6.35mm (1/4")	3	£100.00

**Push Start Oil Free Pneumatic Screwdrivers:**

The New Range of Pneumatic Screwdrivers from Sumake boast a huge range of features only found on more expensive models, they include:

- **Less Noise:** A unique design of the motor reduces the noise level to help prevent occupational disease from noise damage and allowing workers to work more efficiently. This tool is 4dB lower than the last generation and much lower than many other brands.
- **Ergonomic & Comfortable:** Internal high-tech mechanical structure combined with an external thermoplastic grip made from elastomer. 20% lighter than other drivers on the market. Straight type FXF4 series not only has great balance design with a soft grip but also has an anti-reflection appearance. The driver is very practical, ergonomic tool and is very comfortable for the operator to use.
- **Torque Management - External Torque Adjustment Ring:** To adjust the torque rapidly and easily with an outer torque fix system; besides; torque cover can prevent changing the torque by accident.
- **30% Less Counterforce:** The new generation design has a 30% less counterforce and ergonomic grip to improve operator safety and helps reduce occupation injury and RSI.
- **Green Energy/Environmental Protection - Energy Saving:** With a better performance, our tool not only consumes less air thus helping save the environment.
- **High Quality Oil-Free Motor:** A unique design of high quality Oil-Free motor provides a 60% torque increase over the conventional motor.
- Noise levels are between 67 & 72dB depending on model use.
- **Meet ISO5393 & VDI-2647 Standard:** They come complete with 4 extra colour coded torque lock covers (for ease of torque setting identification on larger assembly lines with many drivers).
- High Torque & Low Noise, Push to Start - Auto Shut Off Pneumatic Screwdrivers.
- All these Pneumatic Screwdrivers have a Torque Tolerance of +/- 2%.



Model No	Speed (Rpm)	Torque Range (Nm)	Noise Level (+/-2dB)	Min Air Hose Bore (mm)	Air Consumption (m <sup>3</sup> /min)	Machine Screw (mm)	Screwdriver Bit Size	Quantity Available	Price (Exc. VAT)
FPF4280	250	5.0-28.0	72	8.0	0.45	6.0-11.0	Hex 6.35mm (1/4")	1	£100.00