



Professional Air Tools - Plastic Resin Grip



ST-P7732 1/4"
ST-P7732M 6mm
Mini Air Die Grinder
Speed: 25,000 rpm
- 0.3HP



ST-P7733 1/4"
ST-P7733M 6mm
Air Die Grinder
Speed: 22,000 rpm
- 0.45HP



ST-P7734 1/4"
ST-P7734M 6mm
Mini Air Angle Die Grinder
Speed: 20,000 rpm
- 0.3HP



ST-P7735 1/4"
ST-P7735M 6mm
Air Angle Die Grinder
Speed: 18,000 rpm
- 0.45HP



ST-P6620
Air Metal Shear
Speed: 2,600 rpm



ST-P6622
In-Line Air Scissors
Speed: 2,600 rpm



ST-P6626
Air Nibbler
Speed: 2,600 rpm



ST-P6627
3" Air Cut-off-tool
Speed: 21,000 rpm



ST-P6634 2,600 rpm
Air Smart Eraser
Spindle Thread 5/16"-24



ST-P7738
2" Air Angle Grinder
Speed: 15,000 rpm



ST-P7739
2" Air Angle Sander
Speed: 15,000 rpm

ST-P7736 4" M10x1.5 spindle
ST-P7736A 4-1/2" 5/8x11 spindle
ST-P7737 5" 5/8x11 spindle
100° Angle Grinder
Speed: 10,000 rpm
** W/O Grinding Disc



ST-P7712K

100° Depressed Disc Sander Kit

Contents:

- 1- ST-P7712 1-4" Layered Disc #40
- 1-4" Ripstrip Disc
- 1-4" Multi-Function-Woven Wheel
- 1-High Speed Sanding Pads
4", 4-1/2", 5-1/2"
- 1-4" Wool Wheel
- 1-Handle 1-Nipple 1-Bar
- 1-22mm Nut 1-Blow Case



Specification:

★ Recommend Air Pressure: 6.2bar (90psi)

Model No.	Motor (HP)	Collet Size		Free Speed (r.p.m.)	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
		in	mm		in	mm			cfm	l/min	lbs	kgs	
ST-P7732(M)	0.3	1/4	6	25,000	6-1/10	155	1/4"	3/8"	13	368	0.9	0.43	12Pcs/Ctn/11/0.8'
ST-P7733(M)	0.45	1/4	6	22,000	6-9/10	176	1/4"	3/8"	13	368	1.3	0.60	12Pcs/Ctn/11/0.8'
ST-P7734(M)	0.3	1/4	6	20,000	6-1/10	155	1/4"	3/8"	13	368	1.1	0.53	12Pcs/Ctn/11/0.8'
ST-P7735(M)	0.45	1/4	6	18,000	7	178	1/4"	3/8"	13	368	1.7	0.77	12Pcs/Ctn/12/1.1'

Model No.	Cutting Capacity - Thickness		Free Speed (r.p.m.)	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
	Steel	Aluminum		in	mm			cfm	l/min	lbs	kgs	
ST-P6620	1.2	1.6	2,600	9.4	240	1/4"	3/8"	10	283	2.2	1	12Pcs/Ctn/16/1.1'
ST-P6622	1.2	1.6	2,600	11.4	290	1/4"	3/8"	10	283	2.2	1	12Pcs/Ctn/16/1.1'
ST-P6626	1.2	1.6	2,600	7.6	193	1/4"	3/8"	10	283	2.2	1	12Pcs/Ctn/14/0.8'
ST-P6627	Cutting Wheel Diameter 3"		21,000	7.6	193	1/4"	3/8"	10	283	1.6	0.8	12Pcs/Ctn/13/1.5'

Model No.	Pad/Disc Size		Free Speed (r.p.m.)	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
	inch	mm		in	mm			cfm	l/min	lbs	kgs	
ST-P6634	3-1/2	89	2,600	8.8	225	1/4"	3/8"	10	283	1.8	0.8	12Pcs/Ctn/13/1.1'
ST-P7738	2	51	15,000	7	178	1/4"	3/8"	10	283	1.5	0.7	12Pcs/Ctn/12.4/1.5'
ST-P7739	2	51	15,000	7	178	1/4"	3/8"	10	283	1.5	0.7	12Pcs/Ctn/11.3/0.8'
ST-P7712	-	-	10,000	8.2	210	1/4"	3/8"	19	540	2.86	1.3	12Pcs/Ctn/16/2'
ST-P7736	4	100	10,000	8.2	210	1/4"	3/8"	19	540	3.3	1.5	10Pcs/Ctn/17/1.2'
ST-P7736A	4-1/2	115	10,000	8.2	210	1/4"	3/8"	19	540	3.3	1.5	10Pcs/Ctn/17/1.2'
ST-P7737	5	127	10,000	9.6	244	1/4"	3/8"	19	540	3.85	1.75	12Pcs/Ctn/21/0.8'



Professional Air Tools - Plastic Resin Grip



ST-7841SA
4" Reversible Air Grinder
Speed: 12,000 rpm

ST-7841SB
4" Reversible Air Cutter
Speed: 15,000 rpm



ST-7841SL
4" Extended Reversible Air Cutter
Speed: 15,000 rpm



ST-66342
Non-Vacuum Remove-Pro Tool
With rubber eraser



ST-66342W
Non-Vacuum Remove-Pro Tool
With stripping wheel



ST-66342K
Non-vacuum Remove-pro Tool Kit
Contents:
Each 1 Pc Of Remove-pro Tool
Rubber Eraser
Stripping Wheel
3 Wire Wheels
Adaptor Of Wire Wheel
Hex Wrench



ST-66342V
Self-General Vacuum
Remove-Pro Tool With rubber
eraser, hose & dust bag

ST-66342D
Central Vacuum
Remove-Pro Tool
With rubber eraser



For ST-66342V



With stripping wheel
No. ST-66342VW,
ST-66342DW



66342-100
Rubber Eraser



66342-101
Stripping Wheel
(103mm*30mm)



66342-102
Adaptor for
Rubber Eraser &
Wire Wheel
(No. 66342-103 ~
66342-106)



66342-103
Rubber Eraser



66342-104
0.5mm Straight
Wire Wheel
ø103mmx23mm



66342-105
0.5mm Bend
Wire Wheel
ø103mmx23mm



66342-106
0.7mm Bend
Wire Wheel
ø103mmx23mm

Specification:

★ Recommend Air Pressure 6.2 bar (90psi)

Model No.	Spindle Size	Free Speed (r.p.m.)	Disc Size (in)	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
				in	mm			cfm	l/min	lbs	kgs	
ST-7841SA	5/8"	12,000	4	9.2	234	1/4"	3/8"	19	540	2.4	1.1	12/Ctn/19/1.5'
ST-7841SB	5/8" & 3/8"	15,000	4	9.2	234	1/4"	3/8"	19	540	2.4	1.1	12/Ctn/19/1.5'
ST-7841SL	5/8" & 3/8"	15,000	4	14.8	376	1/4"	3/8"	19	540	3.8	1.7	12/Ctn/21.5/2'

Model No.	Free Speed (r.p.m.)	Overall Length		Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
		in	mm	cfm	l/min	lbs	kgs	
ST-66342(W)	4,090	11	280	10	283	2.47	1.12	4Pcs/Ctn/9kgs/2.1'
ST-66342V(W)	3,950	13-3/4	350	10	283	2.91	1.32	4Pcs/Ctn/10kgs/3'
ST-66342D(W)	3,950	13-3/4	350	10	283	2.91	1.32	4Pcs/Ctn/10kgs/2.1'