



Spring Balancer



SB-1.2 (0.5-1.2kgs)
SB-2.0 (1.0-2.0kgs)
SB-3.0 (2.0-3.0kgs)
SB-4.0 (3.0-4.5kgs) **NEW**
Spring Balancer



SA-2201 (0.3-0.8kgs)
SA-2203 (0.6-1.5kgs)
SA-2203-1 (1.0-2.0kgs)
SA-2204 (1.5-3.0kgs)
SA-2207 (3.0-5.0kgs)
Spring Balancer



SA-2204A (0.8-2.0kgs)
SA-2204B (0.3-1.2kgs)
Nylon rope
Spring Balancer



SA-22015 (0.5-1.5kgs)
Spring Balancer
Plastic Case



SA-22030 (1.5-3.0kgs)
SA-22050 (3.0-5.0kgs)
SA-22070 (5.0-7.0kgs)
Spring Balancer



SA-22090 (5-9kgs)
SA-2215 (9-15kgs)
Spring Balancer



SA-22220 (15-22kgs)
SA-22300 (22-30kgs)
Spring Balancer



SA-22400 (30-40kgs)
SA-22500 (40-50kgs)
SA-22600 (50-60kgs)
SA-22700 (60-70kgs)
Spring Balancer



SA-22900 (70-90kgs)
SA-221050 (90-105kgs)
SA-221200 (105-120kgs)
Spring Balancer

Specification:

Model No.	Capacity (kg)	Travel (m)	Rope		Rope Dia (mm)	Net Weight (kg)	Packing Pcs/Ctn/G.W./Cuft (kgs)
			Sta.	Opt.			
SB-1.2	0.5 - 1.2	1.6		Cable	1.6	0.56	20Pcs/Ctn/12.8/0.95'
SB-2.0	1.0 - 2.0	1.6		Cable	1.6	0.56	20Pcs/Ctn/12.8/0.95'
SB-3.0	2.0 - 3.0	1.6		Cable	1.6	0.56	20Pcs/Ctn/13/0.95'
SB-4.0	3.0 - 4.5	1.6		Cable	1.6	0.56	20Pcs/Ctn/13/0.95'
SA-2201	0.3 - 0.8	1.4	Cable	Nylon	2.5	0.41	40Pcs/Ctn/19.8/1.7'
SA-2203	0.6 - 1.5	1.4	Cable	Nylon	2.5	0.46	40Pcs/Ctn/21/1.7'
SA-2203-1	1.0 - 2.0	1.4	Cable	Nylon	2.5	0.53	40Pcs/Ctn/21/1.7'
SA-2204	1.5 - 3.0	1.4	Cable	Nylon	2.5	0.55	40Pcs/Ctn/22.8/1.6'
SA-2204A	0.8 - 2.0	1.4		Nylon	4	0.57	30Pcs/Ctn/20.1/1.7'
SA-2204B	0.3 - 1.2	1.4		Nylon	4	0.57	30Pcs/Ctn/18.7/1.6'
SA-2207	3.0 - 5.0	1.3		Cable	3.2	0.81	30Pcs/Ctn/24.1/1.7'
SA-22015	0.5 - 1.5	1.3		Cable	2	0.73	20Pcs/Ctn/15.6/1.9'
SA-22030	1.5 - 3.0	1.3		Cable	3.2	1.73	10Pcs/Ctn/18.3/1.7'
SA-22050	3.0 - 5.0	1.3		Cable	3.2	1.82	10Pcs/Ctn/19.2/1.7'
SA-22070	5.0 - 7.0	1.3		Cable	3.2	1.85	10Pcs/Ctn/19.5/1.7'
SA-22090	5.0 - 9.0	1.3		Cable	4.0	3.59	4Pcs/Ctn/15.36/1.9'
SA-2215	9.0 - 15.0	1.3		Cable	4.0	3.61	4Pcs/Ctn/15.44/1.9'
SA-22220	15.0 - 22.0	1.5		Cable	4.8	7.1	3Pcs/Ctn/24/2.5'
SA-22300	22.0 - 30.0	1.5		Cable	4.8	7.9	3Pcs/Ctn/26/2.5'
SA-22400	30 - 40	1.5		Cable	4.8	9.7	1Pcs/Ctn/11/0.9'
SA-22500	40 - 50	1.5		Cable	4.8	10.1	1Pcs/Ctn/11.4/0.9'
SA-22600	50 - 60	1.5		Cable	4.8	11.1	1Pcs/Ctn/12.4/0.9'
SA-22700	60 - 70	1.5		Cable	4.8	11.4	1Pcs/Ctn/12.7/0.9'
SA-22900	70 - 90	2.0		Cable	4.8	22.2	1Pcs/Ctn/25.4/2.1'
SA-221050	90 - 105	2.0		Cable	4.8	23.8	1Pcs/Ctn/27/2.1'
SA-221200	105 - 120	2.0		Cable	4.8	27.4	1Pcs/Ctn/30.6/2.1'



Air Hose Balancer

Features for SA-22015T8 ser. :

- ★ Especially for suspending pneumatic tool. By combining with Hose Reel and Spring Balancer, it achieves neat and orderly production line for enhancing the working efficiency.
- ★ The installation is fast and convenient with 360° install hook. In addition, anti-falling steel wire mounting holes are provided, which must be installed to avoid the failure of the original mounting location.
- ★ Plastic housing is aesthetics and easy cleaning. Smooth braided hose provide easy down-pull stroke. Further, a rubber damper also can stop hose at a fixed height.
- ★ Adopting 8.0 mm inner diameter hose to provide enough air flow to air tool and equipment.



▶ 360° Swivel Hanger



▶ Spiral Drum (Hose Inner Dia. 8mm)



▶ Worm Gear



SA-22015T8 (0.5-1.5 kgs)
SA-22025T8 (1.5-2.5 kgs)
SA-22035T8 (2.5-3.5 kgs)
SA-22050T8 (3.5-5.0 kgs)
SA-22065T8 (5.0-6.5 kgs)

Air Hose Balancer (PU Hose Dia.8x12mm)



SA-22015T (0.5-1.5kgs)
SA-22030T (1.5-3.0kgs)
SA-22050T (3.0-5.0kgs)
Air PU Hose Balancer
(PU Hose Dia:6.5x10mm)

HR-0181 (5x8mmx12M)
HR-0183 (8x12mmx8M)
HR-0185 (6.5x10mmx10M)
Air PU Braid Hose Balancer



SA-2206 (5x8mmx1.2M)
SA-2206A (5x8mmx2M)
Air PU Hose Balancer



Specification:

★ Max Travel 1.0 Mpa(10kgf/cm²)

Model No.	Capacity (kg)		Net Weight (kg)		Travel (m)	Hose Type	Hose Dia (mm)	Air Inlet	Packing Pcs/Ctn/G.W./Cuft (kgs)
	0.5-1.5	1.5-2.5	2.2	2.3					
SA-22015T8	0.5-1.5	1.5-2.5	2.2	2.3	1.3	PU Braid	8 x 12	3/8"	6Pcs/Ctn/14.8/2.5'
SA-22025T8	1.5-2.5	2.5-3.5	2.4	2.4	1.3	PU Braid	8 x 12	3/8"	6Pcs/Ctn/16/2.5'
SA-22035T8	2.5-3.5	3.5-5.0	2.4	2.4	1.3	PU Braid	8 x 12	3/8"	6Pcs/Ctn/16/2.5'
SA-22050T8	3.5-5.0	5.0-6.5	2.5	2.5	1.3	PU Braid	8 x 12	3/8"	6Pcs/Ctn/16.6/2.5'
SA-22015T	0.5-1.5	1.5-3.0	1.8	1.9	1.4	PU Braid	6.5 x 10	1/8"	6Pcs/Ctn/11/1.9'
SA-22030T	1.5-3.0	3.0-5.0	1.9	2.1	1.4	PU Braid	6.5 x 10	1/8"	6Pcs/Ctn/13/1.9'
SA-22050T	3.0-5.0		2.1		1.4	PU Braid	6.5 x 10	1/8"	6Pcs/Ctn/13/1.9'

Model No.	Hose Size (mm)		Max. Working Pressure		Burst Pressure		Hose Length		Hose Type	Working Temperature (°C)	Hose Color	Case Color	Packing Pcs/Ctn/G.W./Cuft (kgs)
	I.D.	O.D.	psi	bar	psi	bar	ft	m					
HR-0181	5	8	200	14	800	56	40	12	PU	-5 ~ +60	Blue	Blue	5 Pcs/Ctn/16/2.54'
HR-0183	8	12	200	14	800	56	27	8	PU	-5 ~ +60	Blue	Blue	5 Pcs/Ctn/17/2.54'
HR-0185	6.5	10	200	14	800	56	33	10	PU	-5 ~ +60	Blue	Blue	5 Pcs/Ctn/16/2.54'
SA-2206	5	8	100	7	400	28	4	1.2	PU	-5 ~ +60	Blue	Grey	10Pcs/Ctn/11/1.4'
SA-2206A	5	8	100	7	400	28	6.6	2	PU	-5 ~ +60	Blue	Grey	10Pcs/Ctn/11/1.4'